

Advanced Trajectories in Industrial Drying Technology (2026–2036)

A Comprehensive Technical and Strategic Assessment



DECARBONIZATION



DIGITALIZATION



PROCESS INTENSIFICATION



ENERGY EFFICIENCY



SUSTAINABLE INDUSTRY



Preface

This technical assessment, “**Advanced Trajectories in Industrial Drying Technology (2026–2036)**,” presents a structured exploration of emerging drying technologies, process intensification, decarbonization, digital twins, AI/ML, multiscale modeling, energy recovery, and industrial scale-up.

The report has been developed from the provided technical source material and refined with assistance from Gemini AI Model, which was used for technical synthesis, organization, analytical structuring, and presentation. The AI-assisted content should be considered a research-support tool; technical claims, numerical values, references, and proposed research directions should be independently verified before use in formal publications, industrial decisions, or academic submissions.

The objective is to provide a forward-looking technical framework for researchers, engineers, and industry professionals working toward more energy-efficient, digitally enabled, and sustainable industrial drying systems.

Advanced Trajectories in Industrial Drying Technology (2026–2036): A Comprehensive Technical and Strategic Assessment

Executive Summary

The decarbonization and digitalization of industrial drying represent a critical frontier in global energy transition and process engineering. Drying operations account for a disproportionate share of industrial energy consumption, a reality fundamentally limited by the latent heat of vaporization of water. This assessment systematically dissects current technological paradigms, rigorously audits proposed macro-trends—including artificial intelligence, digital twins, and advanced heat recovery—and establishes a highly technical research and development roadmap for the 2026–2036 horizon. By integrating multiscale transport phenomena, physics-informed neural networks (PINNs), advanced characterization techniques such as micro-computed tomography, and techno-economic realities localized to specific jurisdictions like Maharashtra, India, the analysis identifies high-value, scalable research vectors capable of achieving NetZero industrial processing. The findings indicate that the most viable pathway eschews speculative hydrogen combustion in favor of advanced mechanical vapor recompression, high-temperature heat pumps utilizing ultra-low global warming potential refrigerants, and thermal energy storage, all orchestrated by dynamically weighted physics-informed surrogate models.

1. Current State of Industrial Drying

Industrial drying remains heavily reliant on fossil-fuel-driven hot-air convective systems, which are inherently plagued by high specific energy consumption and substantial exergy destruction¹. While the fundamental heat and mass transfer mechanisms governing single droplets or ideal porous media are well documented within academic literature, industrial realities dictate that bulk drying processes operate far from thermodynamic equilibrium. Technologies such as rotary, fluidized-bed, and spray dryers exhibit profound spatial and temporal non-uniformities in temperature and humidity fields. Current process control predominantly relies on lagging indicators, such as exhaust temperatures, and heuristic proportional-integral-derivative controllers. This technological stagnation results in systematic over-drying to ensure product microbial safety and moisture limits, which simultaneously degrades temperature-sensitive product quality and squanders immense volumes of high-grade thermal energy. The transition toward sustainable operations requires abandoning these empirical methodologies in favor of deterministic, physics-driven process intensification.

2. Major Technology Paradigm Shifts

The reference material proposes a suite of strategic directions intended to guide the next decade of drying research. A rigorous technical audit of these claims reveals a spectrum of maturity and feasibility, necessitating careful scientific delineation to separate established physical phenomena from speculative industrial claims.

Technology Claim	Classification	Technical Critique & Validation Requirement
High-Temperature Heat Pumps (HTHP)	Emerging Technology	Claims of >160°C output require extensive industrial validation regarding compressor longevity and the thermodynamic stability of low-GWP refrigerants (e.g., R1233zd(E), R1336mzz(Z)) ³ . Laboratory targets frequently ignore realistic sink/source temperature glides.
Mechanical Vapor Recompression (MVR)	Established (Evaporation) / Research (Drying)	Highly established for liquid evaporation, achieving 40–50% energy reductions ⁵ . However, application in solid drying is severely limited by particulate entrainment and droplet-induced impeller erosion ⁷ . Requires advanced gas-solid separation validation.
Superheated-Steam Drying (SSD)	Established (Niche)	Scientifically proven for energy recovery and inert processing. Widespread deployment is hindered by high capital expenditures, rotary valve sealing

		complexities, and unsuitability for highly heat-sensitive biomaterials.
Microwave/RF-Assisted Drying	Emerging Technology	Claims of uniform volumetric heating are physically overgeneralized. The process is highly susceptible to thermal runaway, hot spots, and dielectric property shifts as localized moisture decreases ⁸ . Requires localized multiphysics validation.
Electrohydrodynamic (EHD) Drying	Research-stage	Shows potential for non-thermal preservation of biologicals ¹¹ , but throughput limits, multi-emitter interference, and scale-up feasibility remain highly speculative for bulk industrial tonnage ¹² .
Digital Twins	Emerging Technology	Frequently conflated with basic visualization dashboards. True digital twins require real-time bidirectional data flow and ultra-fast surrogate models. Requires rigorous industrial validation of computational latency ¹³ .
PINNs & AI Soft Sensors	Research-stage	Integrating Navier-Stokes and Darcy flow into neural network loss functions shows immense theoretical promise ¹⁶ , but PINNs suffer

		from severe gradient pathology ("stiffness") near sharp, receding moisture fronts ¹⁸ .
Thermal Energy Storage (TES)	Emerging Technology	Phase Change Materials (PCMs) and sensible heat media (e.g., sand batteries reaching 600°C) provide grid flexibility ¹⁹ . However, thermal cycling stability and supercooling remain practical bottlenecks requiring material science interventions.

3. Scientific Knowledge Gaps

A review of recent literature spanning 2020–2026 highlights severe deficiencies in translating micro-scale physical insights into macro-scale equipment design. First, regarding multiscale transport coupling, while micro-computed tomography has successfully tracked anisotropic shrinkage and pore collapse in geomaterials and biological tissues during dehydration²³, these microstructural deformation metrics are rarely coupled with continuous Eulerian-Eulerian macroscopic models. Second, macroscopic exergy analyses routinely identify combustion and heat exchange as the primary sources of irreversibility¹. However, the micro-scale exergy destruction linked specifically to the phase-change boundary layer, capillary transport resistance, and high-shear atomizer droplet creation is poorly quantified in current literature¹⁹. Finally, most applied machine learning in drying relies on empirical, data-driven regression. These models invariably fail when extrapolated beyond their specific training boundaries, revealing a critical gap in the deployment of physics-constrained network architectures that respect the laws of thermodynamics.

4. AI/ML and Digital Twin Opportunities

The transition from reactive process control to predictive autonomy relies on the deployment of high-fidelity digital twins. A digital twin in this context is not a mere computational fluid dynamics simulation; it is a real-time, bidirectional surrogate model capable of executing predictive control algorithms in milliseconds. The primary opportunity lies in the development of Physics-Informed Neural Networks. By incorporating the governing partial differential equations directly into the neural network's loss function, the model is penalized for predicting non-physical states. However, the application of PINNs to drying introduces a profound mathematical challenge: gradient stiffness. As the evaporation front recedes into a porous

medium, it creates a sharp discontinuity in the moisture concentration gradient. When this sharp front is passed into the backpropagation algorithm of a standard PINN, it causes severe gradient pathology, leading to loss failure and a breakdown of the training process¹⁸. Overcoming this stiffness via adaptive neural tangent kernel weighting or domain-decomposition techniques represents one of the most critical AI research opportunities of the coming decade.

5. NetZero Drying Technologies

Assuming that green hydrogen combustion is the optimal pathway for decarbonizing industrial drying is a deeply flawed heuristic. Direct electrification typically yields superior thermodynamic efficiency. A mathematically rigorous NetZero architecture follows a strict hierarchy of process intensification. The initial stage demands the maximization of mechanical dewatering technologies to physically remove liquid water up to the thermodynamic limit of capillary pressure, thereby bypassing the latent heat penalty entirely. The subsequent thermal drying stage must implement closed-loop architectures. Rather than venting moisture-laden exhaust air, the system must utilize condensation heat recovery. For high-temperature requirements, thermal energy storage utilizing advanced solid media, such as fluidized silica sand beds capable of retaining heat up to 600°C, can decouple the thermal demand of the dryer from the intermittency of renewable electricity generation²¹. This approach fundamentally shifts the energy pathway from fossil-fuel dependence to highly efficient, time-shifted electrified heating.

6. Heat Recovery and Electrification

The electrification of drying relies heavily on two technologies: Mechanical Vapor Recompression and High-Temperature Heat Pumps. MVR systems capture low-pressure exhaust vapor, mechanically compress it using centrifugal impellers, and reinject it as high-temperature heating steam, effectively recycling the latent heat⁶. While MVR is highly mature in liquid evaporation, its application in solid drying is precarious. The exhaust vapor from solid dryers frequently contains entrained micro-particulates and unevaporated liquid droplets. When subjected to the extreme peripheral velocities of an MVR compressor, these droplets cause catastrophic pitting and erosive wear on the impellers, necessitating massive capital expenditures for advanced upstream filtration⁷. Concurrently, the deployment of HTHPs capable of generating sink temperatures above 140°C hinges on the adoption of low-global-warming-potential hydrofluoroolefins, such as R1233zd(E) and R1336mzz(Z)⁴. The chemical stability of these complex refrigerants under continuous high-temperature compression cycles requires rigorous experimental validation to prevent premature compressor failure and systemic efficiency degradation.

7. Process Intensification

Process intensification seeks to bypass the limitations of convective heat transfer by delivering energy directly to the internal moisture of the material. Microwave and radio-frequency assisted drying accomplish this via volumetric dielectric heating. However, the deployment of electromagnetic fields introduces severe non-linearities. As a material dries, its dielectric loss

factor decreases. If a localized region dries faster than the bulk, it absorbs less energy, which theoretically implies a self-leveling effect; however, in complex biomaterials, localized bound water and salt concentrations can paradoxically increase the loss factor at elevated temperatures. This phenomenon triggers thermal runaway, where a localized hot spot rapidly absorbs surrounding electromagnetic energy, leading to catastrophic internal charring and product failure⁸. Research must focus on integrating real-time dielectric sensing with highly responsive solid-state microwave generators to dynamically shift frequencies and prevent runaway conditions.

8. Multiscale Drying Science

The fundamental science of drying is governed by phenomena occurring at the pore scale. The transition from the constant-rate drying period to the falling-rate period corresponds physical to the recession of the liquid-vapor meniscus into the porous network of the material. During this phase, moisture transport shifts from liquid capillary action to Knudsen diffusion and vapor transport. As capillary tension increases, the solid matrix is subjected to immense internal stresses. Advanced characterization techniques, specifically in-situ micro-computed tomography, have become essential for visualizing this structural evolution²³. By mapping the anisotropic shrinkage, pore collapse, and glass transition dynamics of materials in real-time, researchers can extract highly accurate permeability tensors²⁶. These localized tensors must then be upscaled using Lattice Boltzmann methods to feed macroscopic continuum models, thereby closing the gap between fundamental physics and industrial equipment modeling²⁶.

9. Industrial Scale-Up Challenges

A persistent failure in drying research is the inability to translate laboratory success to industrial tonnage. A phenomenological model validated on a 10-gram thin-layer sample in a precision laboratory oven frequently fails catastrophically when applied to a 10-tonne-per-hour continuous rotary dryer. The dominant scale-up variables are macroscopic rather than microscopic. In industrial equipment, the residence time distribution of the particulate phase is highly heterogeneous. Particles experience varying degrees of wall friction, inter-particle collisions, and gas-channeling, leading to massive temperature and humidity gradients across the drying chamber. Furthermore, in systems like spray dryers, the overlapping of multiple atomization cones creates complex droplet collision and coalescence dynamics that simply do not exist in single-droplet laboratory studies. Rigorous scale-up requires the deployment of coupled Computational Fluid Dynamics and Discrete Element Method simulations to accurately map these macroscopic transport limitations before physical construction begins.

10. Experimental Research Framework

Establishing the scientific foundation for the next generation of drying technology requires a highly controlled, sensor-rich experimental framework. The laboratory apparatus must consist of a closed-loop convective tunnel dryer instrumented with Coriolis mass flow meters, precision chilled-mirror hygrometers for absolute humidity measurement, and high-speed infrared

thermography to track transient surface temperatures. The experimental design must reject traditional one-factor-at-a-time methodologies in favor of Response Surface Methodology utilizing a Central Composite Design. Independent variables must include inlet dry-bulb temperature, superficial gas velocity, absolute humidity, and characteristic particle diameter. The primary dependent response variables will include the specific energy consumption, the critical moisture content denoting the onset of the falling-rate period, and the volumetric shrinkage quantified via intermittent micro-CT scanning. Statistical significance must be rigorously established utilizing Analysis of Variance to generate robust quadratic surrogate models for early-stage process optimization.

11. Mathematical Modeling Framework

The core mathematical representation of the drying process must solve the highly coupled, non-linear partial differential equations governing momentum, heat, and mass transfer within a shrinking porous domain.

The mass conservation equation for liquid water must incorporate both capillary pressure gradients and concentration-driven diffusion:

$$\frac{\partial(\rho_s X)}{\partial t} + \nabla \cdot (v_s \rho_s X) = \nabla \cdot (D_{eff} \rho_s \nabla X) - \dot{m}_{evap}$$

The energy conservation equation must account for the latent heat of vaporization acting as a volumetric heat sink at the moving phase-change boundary:

$$\frac{\partial(\rho_{eff} c_{p,eff} T)}{\partial t} + \nabla \cdot (\rho_{eff} c_{p,eff} v T) = \nabla \cdot (k_{eff} \nabla T) - \dot{m}_{evap} \Delta H_{vap}$$

Crucially, the effective transport coefficients (D_{eff} , k_{eff}) are not static; they are highly non-linear functions of local temperature, moisture content, and the transient porosity tensor dictated by the material's thermo-mechanical shrinkage. The boundary conditions at the solid-gas interface must explicitly model the local convective heat and mass transfer coefficients, which dynamically alter as the surface morphology deforms.

12. AI/ML Framework

To deploy the aforementioned mathematical models in real-time control systems, they must be translated into AI architectures. The Physics-Informed Neural Network framework forces the neural network to satisfy the governing PDEs. The composite loss function ($\mathcal{L}_{total}$) is formulated as:

$$\mathcal{L}_{total} = \lambda_{data} \mathcal{L}_{data} + \lambda_{PDE} \mathcal{L}_{PDE} + \lambda_{IC} \mathcal{L}_{IC} + \lambda_{BC} \mathcal{L}_{BC}$$

Where $\mathcal{L}_{data}$ represents the mean squared error against physical sensor readings, and $\mathcal{L}_{PDE}$ represents the residual of the mass and energy conservation equations evaluated at collocation points across the spatiotemporal domain. Because the sharp moisture gradients induce gradient pathology during backpropagation¹⁸, researchers must investigate dynamic weighting schemes (λ) based on the eigenvalues of the Neural Tangent Kernel, ensuring that the network optimizes uniformly across both the highly dynamic drying front and the relatively stable internal core of the material.

13. Exergy Analysis

A robust thermodynamic assessment must differentiate between total energy consumption and exergy destruction. Exergy represents the maximum useful work attainable as a system approaches equilibrium with its environment. The exergy balance is defined as:

$$\dot{Ex}_{in} = \dot{Ex}_{out} + \dot{Ex}_{loss} + \dot{Ex}_{destruction}$$

Advanced exergetic analysis must be applied to isolate *avoidable* versus *unavoidable* exergy destruction. For example, in a conventional spray dryer, the immense shear forces and pressure drops required for atomization result in massive, largely unavoidable exergy destruction¹⁹. Conversely, the exergy destroyed by mixing high-temperature combustion gases with ambient dilution air is entirely avoidable. The strongest thermodynamic research opportunity lies in evaluating closed-loop superheated-steam dryers coupled with MVR. By eliminating the non-condensable carrier gas (air), the system bypasses the unavoidable exergy destruction associated with heating inert nitrogen, allowing the MVR compressor to recover nearly the entirety of the exhaust exergy⁶.

14. TEA Framework

Techno-economic viability must be mapped precisely to local boundary conditions to possess any industrial relevance. Assuming a facility operating within the Maharashtra State Electricity Distribution Company Limited (MSEDCL) jurisdiction, the economic modeling must incorporate complex tariff structures²⁹.

Economic Parameter	MSEDCL Boundary Condition (FY2026-27)	Impact on Dryer Feasibility

Industrial Energy Tariff	₹7.66 / kWh (LT-V Industry) ³⁰	High base cost strongly incentivizes MVR and HTHP deployment if COP > 3.0.
Fixed Demand Charges	₹420 / kW / month ³⁰	Heavily penalizes oversized compressor motors; requires precise load matching.
Time of Day (ToD) Tariffs	Premium rates during peak evening hours ³¹ .	Mandates the integration of Thermal Energy Storage (TES) to shift electrical heating loads to off-peak or high-solar windows.
Regulatory Classification	District cooling/heating systems categorized as Industrial ³² .	Favorable categorization for large-scale, centralized heat pump deployments sharing thermal networks.

The Levelized Cost of Drying must be calculated by amortizing the high initial CAPEX of MVR and HTHP equipment against the operational savings generated by these localized tariff structures.

15. LCA Framework

The Life-Cycle Assessment framework must establish a rigorous cradle-to-gate system boundary. Evaluating an electrified dryer against a fossil-fuel dryer requires a dynamic assessment of the grid carbon intensity. In regions heavily reliant on coal thermal power, shifting a drying process from direct natural gas combustion to grid electricity via a heat pump may paradoxically increase the primary energy demand and Scope 2 global warming potential. The LCA must dynamically calculate the break-even Coefficient of Performance required to achieve actual carbon reductions. Furthermore, the framework must explicitly account for the environmental penalty of refrigerant leakage from the HTHP systems⁴, driving the necessity for utilizing natural refrigerants (such as ammonia or supercritical carbon dioxide) or advanced hydrofluoroolefins to ensure the overall sustainability metrics remain positive.

16. 20+ PhD Research Topics

The following proposed PhD topics represent highly specific, industrially relevant research vectors that address the critical knowledge gaps identified in this assessment.

#	Research Title	Scientific Problem	Novelty & Methodology
1	Overcoming Gradient Stiffness in PINNs at the Evaporation Front	Neural networks fail to converge at sharp, moving phase-change boundaries ¹⁸ .	Development of domain-decomposed loss functions and dynamic weighting algorithms.
2	Exergoeconomic Analysis of MVR-Assisted Superheated Steam Drying	Inability to allocate exact thermodynamic costs to complex vapor recycling loops ⁵ .	Advanced exogenous/endogenous exergy cost matrices.
3	Micro-CT Quantification of Anisotropic Pore Collapse during Glass Transition	Lack of physical data linking T_g to microstructural failure in real-time ²³ .	In-situ μ -CT during convective heating; extraction of transient permeability tensors.
4	Erosion Mitigation in High-Speed MVR Impellers under Droplet Impact	High-speed droplet impact causes severe fatigue and erosion in vapor compressors ⁷ .	Coupled CFD-particle tracking and material fatigue modeling.
5	Bayesian Optimization of Multiscale CFD-DEM for Fluidized Bed Scale-up	The computational expense of CFD-DEM prevents rapid multi-objective optimization.	Surrogate-assisted Bayesian framework ³³ minimizing specific energy consumption.

6	Thermal Energy Storage Dynamics using Nanoparticle-Doped PCMs	Intermittency of renewable heat inputs requires buffering with poor thermal conductors ²⁰ .	Transient thermal response modeling of carbon-nanotube-enhanced molten salts.
7	Electrohydrodynamic (EHD) Drying Kinetics of Thermolabile Pharmaceuticals	Scale-up limitations and multi-emitter electric field instability ¹¹ .	Multi-physics mapping of corona discharge interference; improved bulk throughput.
8	Multi-Objective NSGA-II Optimization of Primary Vacuum Sublimation	Extreme energy intensity of maintaining ultra-low pressures in freeze-drying ³⁶ .	Dynamic shelf-temperature profiling balancing chamber pressure against product collapse risk.
9	Dielectric Shift Mitigation to Prevent Thermal Runaway in Microwave Drying	Unpredictable loss factor changes cause catastrophic localized charring ⁸ .	Deep reinforcement learning for real-time frequency and power tuning based on IR thermography.
10	Multiphysics Modeling of Bound Water Diffusion in Hygroscopic Polymers	Breakdown of standard Fickian diffusion models near absolute zero moisture.	Implementation of Maxwell-Stefan diffusion models for non-ideal macromolecular matrices.

11	Thermodynamic Stability of R1233zd(E) in >140°C HTHP Drying Cycles	Degradation of low-GWP refrigerants at high industrial evaporation temperatures ⁴ .	Long-term thermodynamic property mapping and compressor lubrication compatibility testing.
12	Acoustic Soft Sensors for Real-Time Agglomeration Tracking in Spray Dryers	Optical sensors fail instantly due to chamber fouling, causing lagging detection.	Machine learning applied to acoustic emission spectra for instant particle size distribution detection.
13	Fractional-Order Calculus Modeling of Viscoelastic Drying Shrinkage	Standard Newtonian models fail to capture polymer creep during intense drying.	Highly accurate structural deformation predicting macro-scale crust formation and cracking.
14	Dynamic LCA of Hybrid Solar-Biomass Dryers under Variable Grid Intensity	Static LCAs misrepresent the true carbon impact of intermittent, grid-tied operation.	Time-resolved LCA frameworks integrating real-time regional marginal emissions factors.
15	Deep Reinforcement Learning for Autonomous Rotary Dryer Control	Unpredictable stochastic feed variations cause severe over/under drying.	Autonomous DRL agent trained to continuously manipulate drum tilt and counter-current airflow.

16	Phase-Field Modeling of Capillary Transport in Heterogeneous Media	Macroscopic Darcy approximations fail fundamentally at the pore-throat scale.	Fundamental mapping of transient liquid topology using localized Lattice Boltzmann Methods ²⁶ .
17	Superheated Steam Drying of Biomass: Kinetics of Tar Condensation	Condensation of volatile organics fouls heat exchanger surfaces, destroying efficiency.	Reaction kinetics and thermal conductivity degradation models of complex biological fouling layers.
18	Exergy Destruction Minimization in Twin-Fluid Atomizers	Massive exergy loss occurs during high-shear liquid droplet formation ¹⁹ .	Internal nozzle geometry optimization utilizing adjoint shape optimization algorithms.
19	Techno-Economic Optimization of Peak-Shaving via MSEDCL ToD Tariffs	Time-of-Day tariffs heavily penalize peak industrial operation ³¹ .	MPC strategies utilizing sensible sand battery thermal inertia to shift electrical loads to off-peak zones.
20	Non-Equilibrium Thermodynamics of Surface Crust Formation	Standard boundary conditions assume equilibrium, failing to predict severe case hardening.	Modified mass transfer boundary formulations integrating local resistance and concentration jumps.

17. Laboratory Experimental Program

To establish the requisite scientific foundation, the laboratory experimental program must be exhaustively instrumented. Assume access to a convective tunnel dryer equipped with precision load cells, chilled-mirror hygrometers, high-resolution thermal imaging, and intermittent access to an X-ray micro-computed tomograph. The independent variables will include inlet air temperature (40–90°C), superficial gas velocity (0.5–2.5 m/s), and controlled relative humidity (10–40%). The primary dependent variables are the transient moisture ratio, specific energy consumption, and volumetric shrinkage. The methodology requires a minimum of three replicates per condition within a Box-Behnken design to map the response surfaces. The expected trends should demonstrate that higher temperatures accelerate the onset of the falling-rate period, but simultaneously trigger premature surface crusting (case hardening) which subsequently retards the internal effective diffusivity, a phenomenon that will be visually verified through the micro-CT scans documenting pore collapse.

18. Pilot-Scale Program

The transition to pilot-scale (approximately 50–100 kg/hr throughput) is critical for validating the macroscopic transport models. The pilot program will utilize a continuous fluidized-bed dryer integrated with a closed-loop High-Temperature Heat Pump utilizing an R1233zd(E) refrigerant cycle⁴. The primary independent variables include feed rate, weir height (dictating residence time), and the heat pump compressor frequency. The dependent variables are the final product moisture variance and the system-wide Coefficient of Performance. The statistical analysis will rely on continuous time-series data to validate the dynamic response capabilities of the PINN-based Model Predictive Controller when subjected to artificial feed-moisture step disturbances. The expected outcome is a controller capable of rejecting stochastic disturbances while maintaining a system COP greater than 3.5.

19. 2026–2036 R&D Roadmap

The strategic timeline for achieving full commercialization and NetZero operation spans five distinct phases over the coming decade.

- **Phase I: 2026–2028 (Fundamental Physics & Sensorization)**

- *Objectives:* Map anisotropic shrinkage using in-situ μ -CT; establish baseline multiscale exergy destruction vectors.
- *Technologies:* Laboratory convective systems, Lattice Boltzmann pore modeling.
- *TRL:* 2–4.
- *Major Risks:* Inability to accurately extract permeability tensors from highly deformed micro-CT voxels.

- **Phase II: 2028–2030 (AI/ML Integration)**

- *Objectives:* Develop and train PINNs using Phase I physics. Overcome boundary stiffness in neural training algorithms¹⁸.

- *KPIs*: Surrogate models running < 50 milliseconds with $< 5\%$ error against rigorous, highly expensive CFD models.
- *TRL*: 4-5.
- **Phase III: 2030–2032 (Pilot-Scale Hybridization)**
 - *Objectives*: Integrate HTHP and MVR systems into a fully operational 100 kg/hr pilot facility.
 - *Technologies*: Low-GWP heat pumps, particulate-resistant MVR blowers⁷.
 - *KPIs*: Continuous operation demonstrating a system COP > 4.0 .
- **Phase IV: 2032–2034 (Digital Twin Deployment)**
 - *Objectives*: Implement full Model Predictive Control via the PINN digital twin on the physical pilot system.
 - *KPIs*: Autonomous rejection of feed disturbances without human intervention; 25% verified reduction in specific energy consumption compared to PID baselines.
- **Phase V: 2034–2036 (Industrial Tonnage & NetZero Autonomy)**
 - *Objectives*: Scale the architecture to a 1+ tonne/hr industrial manufacturing site. Fully couple renewable energy, massive thermal energy storage (e.g., sand batteries)²¹, and intelligent Time-of-Day load shifting.
 - *KPIs*: Validated NetZero operational cycle (encompassing Scope 1 and 2 emissions) and widespread commercialization of generated intellectual property.

20. Publication Strategy

The publication strategy segments outputs to maximize impact factor and disciplinary reach, ensuring rigorous peer review of every core technology claim.

- **Fundamental Papers**: Targeted at the *International Journal of Heat and Mass Transfer*³⁷.
Focus: μ -CT analysis of pore collapse and non-Fickian capillary transport mechanisms. Minimum evidence: 3D voxel data and rigorous statistical validation of proposed PDE models.
- **Modeling Papers**: Targeted at *Chemical Engineering Science*²⁶ or the *AIChE Journal*.
Focus: Novel PINN architectures overcoming gradient stiffness during phase change. Minimum evidence: Mathematical convergence analysis and computational speed-up metrics versus traditional finite volume methods.
- **Sustainability & Exergy**: Targeted at *Applied Energy*¹³ or *Energy*¹. Focus: Advanced exogenous and endogenous exergy destruction matrices for MVR-HTHP systems. Minimum evidence: Detailed thermodynamic state mapping and empirically verified compressor efficiencies.
- **Industrial Papers**: Targeted at *Drying Technology*¹¹. Focus: Scale-up validation of the PINN digital twin at the pilot scale. Minimum evidence: Real-time control trend logs and verified product quality retention under dynamic loads.

21. Patent Opportunities

Identifying and protecting novel intellectual property is crucial for technology commercialization.

1. **Hybrid HTHP-MVR Exhaust Recovery Apparatus:** A physical configuration utilizing a preliminary high-temperature heat pump coil to strip latent heat, followed by an MVR compressor optimized for high-particulate saturated steam. This design bypasses traditional droplet erosion mechanisms in MVR impellers⁷. *Proof required:* Empirical evidence of prolonged impeller lifespan and sustained system COP.
2. **PINN-Driven Predictive Controller for Volumetric Runaway:** A control logic patent utilizing high-frequency thermal-camera data layers fed directly into a PINN to proactively detune microwave magnetrons milliseconds before thermal runaway occurs. *Proof required:* Demonstration of un-charred product in historically highly volatile, structurally complex feedstocks⁸.
3. **Acoustic-Emission Soft Sensor for Spray Dryer Agglomeration:** A hardware-software apparatus utilizing machine learning to analyze the acoustic signatures of colliding particles within a spray dryer, allowing for real-time adjustments to atomization pressure before catastrophic wall-fouling occurs. *Proof required:* High correlation ($R^2 > 0.9$) between acoustic signatures and offline laser diffraction particle size analysis.

22. Industrial Collaboration Opportunities

The research must be tailored to the specific challenges of dominant industrial sectors.

- **Food and Dairy:** Dominated by massive spray drying operations. The primary product-quality challenges are protein denaturation and powder flowability¹¹. The most promising decarbonization pathway is integrating MVR on the exhaust and HTHPs for inlet air pre-heating. The primary AI opportunity is real-time acoustic agglomeration tracking.
- **Pharmaceuticals:** Dominated by batch fluidized bed and freeze drying. The primary challenges are maintaining API polymorphic stability and strict regulatory compliance. The decarbonization pathway relies on closed-loop heat pump drying with stringent cross-contamination controls. The AI opportunity is the deployment of digital twins to achieve real-time, non-destructive batch release.
- **Specialty Chemicals:** Characterized by rotary and flash dryers handling hazardous solvents. The challenge is minimizing extremely high specific energy consumption while maximizing solvent recovery. The decarbonization pathway is closed-loop superheated steam drying coupled with MVR for continuous solvent regeneration.

23. Red-Team Assessment

A critical "red-team" evaluation of the preceding roadmap reveals several vulnerabilities and overly optimistic assumptions that must be actively managed.

- **Weak Assumptions:** The assumption that PINNs will universally outperform empirical models in highly stochastic industrial environments (where unmeasured disturbances like

raw feedstock biochemical composition fluctuate wildly) is dangerous. If the physical PDE boundaries are constantly shifting in ways the model cannot measure, the PINN will inevitably fail.

- **Overhyped Technologies:** Electrohydrodynamic (EHD) drying and low-frequency ultrasound are academically popular but fundamentally lack the volumetric penetration depth necessary for bulk industrial throughput¹². They are unlikely to scale beyond high-value thin films.
- **Hidden CAPEX Penalties:** MVR systems require exceptionally clean vapor streams. The CAPEX of the cyclonic or electrostatic precipitation necessary to protect the MVR impeller from catastrophic droplet erosion⁷ may completely negate the OPEX energy savings.
- **Emissions Shifting:** Deploying electrically driven heat pumps in regions where the grid is dominated by coal thermal power increases primary energy demand and emissions compared to direct natural gas combustion. Claims of "zero carbon" are invalid unless local renewable generation and thermal energy storage are explicitly integrated²².

24. Final Research Questions

Synthesizing this exhaustive analysis, the following integrated research programs combine fundamental drying science, advanced experimentation, AI/ML, and rigorous sustainability analysis. These programs are specifically tailored to the industrial and economic realities of hubs like Mumbai and Pune, Maharashtra, to form the basis of a long-term university-industry R&D strategy from 2026 to 2036.

1. **The "ToD-Optimized" Hybrid Heat Pump Program:** How can Time-of-Day (ToD) electricity tariffs in Maharashtra³¹ be leveraged to optimize the Levelized Cost of Drying? This program develops a dynamic control twin for an HTHP dryer combined with high-temperature sand battery thermal storage²¹. The fundamental science focuses on storage media heat transfer kinetics, while the AI optimizes thermal charging exclusively during off-peak windows, yielding a highly favorable LCA and TEA profile.
2. **Multiscale PINN Digital Twin for Pharmaceutical Fluid-Beds:** How can we mathematically resolve the moving-boundary stiffness problem in PINNs to accurately predict intra-particle moisture and prevent API polymorphic degradation? This program integrates μ -CT mapping of excipient matrices with computational fluid dynamics, directly targeting the stringent quality requirements of the high-value Indian pharmaceutical export sector.
3. **Fouling-Resistant MVR Superheated Steam Architectures:** What are the precise aerodynamic conditions required to mitigate impeller erosion⁷ and heat exchanger fouling in MVR systems processing biomass/agricultural waste? The scientific core investigates the multiphase physics of droplet impingement and develops robust separation algorithms and exergetically optimal vapor compression cycles.
4. **Electro-Dielectric Runaway Mitigation in Hybrid RF Drying:** How can real-time spatial thermal imaging be fused with deep reinforcement learning to prevent volumetric thermal

runaway⁸ in microwave-assisted convective drying? This research focuses on training an autonomous agent capable of predicting localized dielectric shifts and manipulating magnetron frequencies instantaneously to preserve the cellular structure of high-value agricultural exports.

5. **Exergoeconomic Valorization of Dairy Spray Drying:** How can advanced avoidable/unavoidable exergy destruction modeling¹⁹ be coupled with NSGA-II multiobjective optimization³³ to retrofit India's massive dairy processing infrastructure⁴²? This program aims to mathematically minimize the specific energy consumption while strictly preserving whey protein structural integrity through the integration of cascaded exhaust heat recovery and AI-driven acoustic soft sensors.

Works cited

1. Exergy, energy, exergoenvironmental assessment of a novel, <https://jten.yildiz.edu.tr/storage/upload/pdfs/1769786038-en.pdf>
2. Energies, Volume 16, Issue 12 (June-2 2023) – 300 articles, <https://www.mdpi.com/1996-1073/16/12>
3. HEAT PUMPS IN THE EUROPEAN UNION – JRC Publications, https://publications.jrc.ec.europa.eu/repository/bitstream/JRC134991/JRC134991_01.pdf
4. Uluslararası Sürdürülebilir Mühendislik ve Teknoloji Dergisi -IJSET, <https://dergipark.org.tr/tr/download/issue-file/95705>
5. Mechanical Vapor Recompression (MVR) Compressors Market Size, <https://www.businessresearchinsights.com/market-reports/mechanical-vapor-recompression-mvr-compressors-market-100265>
6. Mechanical Vapor Recompression (MVR) Compressor Market, <https://dataintelo.com/report/mechanical-vapor-recompression-mvr-compressor-market>
7. Experimental Investigation on the Erosion Resistance ... – Scilit, <https://www.scilit.com/publications/27182c440725ba044332876584e1c829>
8. Now & Future 2024 – RD20, https://rd20.aist.go.jp/wp-content/uploads/2025/03/2024_6th_NowFuture_r.pdf
9. 9 6<032=-80 ¥52'2:,6.2:(37=(– zastosowania elektromagnetyzmu, https://ptze.pl/wp-content/uploads/2025/10/PTZE_2025_materialy-konferencyjne_Jaroszowice_.pdf
10. Unified Classical Resonance Model (UCRM) – Zenodo, [https://zenodo.org/records/19144052/files/Unified%20Classical%20Resonance%20Model%20\(UCRM\)%203.21.2026%20%20V1.2.pdf?download=1](https://zenodo.org/records/19144052/files/Unified%20Classical%20Resonance%20Model%20(UCRM)%203.21.2026%20%20V1.2.pdf?download=1)
11. P.01 AI-Driven Surrogate Models for Fermentation – Effost conference, <https://effostconference.com/wp-content/uploads/Abstract-book-posters-1.pdf>
12. Optimization of Pre-Treatments to Overcome Stickiness-Related, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12571961/>

13. Energies, Volume 19, Issue 13 (July-1 2026) – 278 articles, <https://www.mdpi.com/1996-1073/19/13>
14. Annual Report 2024 - DTU Chemical Engineering, [https://www.kt.dtu.dk/-/media/institutter/kemiteknik/nyt-design23/annual-reports-og-gsy/7500531 annual report 2024 web1.pdf](https://www.kt.dtu.dk/-/media/institutter/kemiteknik/nyt-design23/annual-reports-og-gsy/7500531%20annual%20report%2024%20web1.pdf)
15. (PDF) Digital Transformation in Water Organizations - ResearchGate, [https://www.researchgate.net/publication/361671566 Digital Transformation in Water Organizations](https://www.researchgate.net/publication/361671566_Digital_Transformation_in_Water_Organizations)
16. application of particle swarm optimization and artificial neural network, [https://www.researchgate.net/publication/395722378 Nanoparticle aggregation impact on nanofluid flow in a rotating horizontal annulus application of particle swarm optimization and artificial neural network](https://www.researchgate.net/publication/395722378_Nanoparticle_aggregation_impact_on_nanofluid_flow_in_a_rotating_horizontal_annulus_application_of_particle_swarm_optimization_and_artificial_neural_network)
17. Numerical stability analysis for the trapezoidal fin - ResearchGate, [https://www.researchgate.net/figure/Numerical-stability-analysis-for-the-trapezoidal-fin fig41 398621842](https://www.researchgate.net/figure/Numerical-stability-analysis-for-the-trapezoidal-fin_fig41_398621842)
18. Report and Research Highlights, [https://www.shiae.cuhk.edu.hk/sites/default/files/2025-03/shiae report and research highlights 2020-2024.pdf](https://www.shiae.cuhk.edu.hk/sites/default/files/2025-03/shiae_report_and_research_highlights_2020-2024.pdf)
19. 10 – 11 April 2024 Messecongress Graz Austria - AEE Intec, [https://www.aee-intec.at/wp-content/uploads/2025/05/Conference Proceedings ISEC 2024.pdf](https://www.aee-intec.at/wp-content/uploads/2025/05/Conference_Proceedings_ISEC_2024.pdf)
20. Thermal Energy Storage Technologies: A Review of, <https://f1000research.com/articles/15-83>
21. Sand Battery (Thermal Storage) Market Size, Growth [2035], <https://www.astuteanalytics.com/industry-report/sand-battery-market>
22. Investigation of Beeswax–Calcite Microcapsules as PCM for Latent, <https://pmc.ncbi.nlm.nih.gov/articles/PMC12734866/>
23. Експорт към MS Word - Институт по физикохимия - БАН, [https://ipc.bas.bg/media/DOCUMENTI/Godishni otcheti/2023/%D0%A6%D0%B8%D1%82%D0%B0%D1%82%D0%B8%202023.pdf](https://ipc.bas.bg/media/DOCUMENTI/Godishni_otcheti/2023/%D0%A6%D0%B8%D1%82%D0%B0%D1%82%D0%B8%202023.pdf)
24. (PDF) A Novel Method of Measuring Moisture Content Distribution in, [https://www.researchgate.net/publication/241736494 A Novel Method of Measuring Moisture Content Distribution in Timber During Drying Using CT Scanning and Image Processing Techniques](https://www.researchgate.net/publication/241736494_A_Novel_Method_of_Measuring_Moisture_Content_Distribution_in_Timber_During_Drying_Using_CT_Scanning_and_Image_Processing_Techniques)
25. SICB 2025 Annual Meeting Abstracts, <https://www.vliz.be/imisdocs/publications/413968.pdf>
26. Dominique Derome - Spécialistes - Université de Sherbrooke, <https://www.usherbrooke.ca/recherche/fr/specialistes/details/dominique.derome>
27. Mechanical vapor Recompression (MVR) - France Evaporation, <https://www.evaporation.com/en/industries/decarbonization/mechanical-vapour-recompression-mvc-mvr/>
28. A Review on Cooling Systems for Portable Energy Storage Units, <https://www.mdpi.com/1996-1073/16/18/6525>
29. Maharashtra Electricity Tariff 2026-27 — ₹1.90–13.97/unit,

- <https://thediscombill.com/tariffs/maharashtra/>
30. Maharashtra Electricity Tariff 2026 | 1 Unit Rate, <https://electricbill.in/en/tariffs/maharashtra>
 31. Maharashtra Electricity Tariff 2025-26 | PDF - Scribd, <https://www.scribd.com/document/869024051/Tariff-Revision-for-FY-2025-26-to-FY-2029-30>
 32. MERC Classifies District Cooling Systems Under Industrial Tariff, <https://www.saurenergy.com/solar-energy-news/maharashtra-merc-classifies-district-cooling-systems-under-industrial-tariff-12049593>
 33. Processes, Volume 14, Issue 12 (June-2 2026) – 186 articles – MDPI, <https://www.mdpi.com/2227-9717/14/12>
 34. Latest articles – MDPI, https://www.mdpi.com/latest_articles
 35. Phase Change Microcapsules Market 2026 – 24ChemicalResearch, <https://www.24chemicalresearch.com/reports/305561/phase-change-microcapsules-market>
 36. Machine learning (ML) and deep learning (DL) in sustainable, <https://www.tandfonline.com/doi/full/10.1080/13467581.2025.2574571>
 37. Publication Details – R&D Section | IIT Indore, https://rnd.iiti.ac.in/publication_rnd
 38. Dr Elliot J. Carr | Lecturer and Researcher in Applied and, <https://elliottcarr.github.io/>
 39. Cover 2025 .cdr, https://files.iittp.ac.in/pdfs/annualreport/Hindi_Annual_Report_2024_25.pdf
 40. Faculty Profiles – KYAW THU, https://hyoka.ofc.kyushu-u.ac.jp/html/100021716_en.html
 41. Proceedings of the 18th International Symposium on, <https://drustvo-informatika.si/uploads/documents/d61da7b6-eb3d-4b27-bed5-3c93190ac3de/SOR25Proceeding.pdf>
 42. Sanggahan dan Batasan Tanggung Jawab – IDX, https://www.idx.co.id/StaticData/NewsAndAnnouncement/ANNOUNCEMENTSTOCK/From_EREP/202604/73044b043c_1da3f73d59.pdf
 43. Acknowledgements – Sustainable Development Solutions Network, <https://files.unsdsn.org/AGF%20-%20Malaysia%202.2%20Report%20-%20FINAL.pdf>
 44. INEOS QUATTRO HOLDINGS LIMITED 2025 ANNUAL REPORT, <https://www.ineos.com/globalassets/investor-quattro-ir/public/annual-reports/ineos-quattro-holdings-limited---annual-report-2025.pdf>